

PHYSICO-CHEMICAL PROPERTIES OF SEWAGE SLUDGE AND ITS IMPACT ON SOIL FERTILITY

Praveen Solanki¹, Baby Akula², S. Harish Kumar Sharma³,

D. Jagdishwar Reddy⁴

¹Dept. of Environmental Science & Technology, College of Agriculture, R. Nagar,

²Dept. of Soil Science & Agricultural Chemistry, College of Agriculture, R. Nagar

Acharya N.G. Ranga Agricultural University, Rajendranagar, Hyderabad

ABSTRACT

Introduction- Recognized as a valuable resource, sewage sludge could be recycled as fertilizer and soil improvement material for land because it consists largely of organic substances and also contains N and P, which are the main nutrimental elements of plants and soil fertility. However, sewage sludge consists of not only valuable components such as nutrients but also heavy metals. This paper reports the physico-chemical properties of sewage sludge (obtained from NMK-STP, Hyderabad) and its impact on soil fertility as a soil health amendment. A total of seven potting media were prepared containing soil, sewage sludge and different ratios of soil + sewage sludge.

Results- Results indicated that sewage sludge can be safely used as a rich organic matter for realizing better soil properties as ecofriendly manners instead of inorganic fertilizers. Among treatments, T₅ was found to be significantly superior in all observed parameters. The physico-chemical and chemical characteristics of sewage sludge were done which indicated that it was moderately acidic (pH 5.81) in nature. EC was 5.48 dS m⁻¹ and total organic carbon was 25.76 per cent. Total N, P and K contents of sewage sludge were 3.29, 1.23 and 2.98 %, respectively. The triacid extractable zinc, in sewage sludge was 27.72 mg kg⁻¹. The diacid extractable heavy metals viz., Cd, Co, Ni and Pb were accordingly 0.97, 0.37, 1.69 and 6.86 mg kg⁻¹. All the heavy metals were within maximum permissible limits as per the USEPA standards.

Conclusion- It was concluded that addition of sewage sludge, in appropriate quantities, to potting media has synergistic effects on soil physico-chemical properties, its organic matter content and nutrient status.

Purpose- The purpose of this study were (1) to analyse the properties of sewage sludge and soil (2) to assess the potential for using sewage sludge as an organic alternative to chemical fertilizers for improving soil properties and fertility status.

Keywords: Sewage Sludge, Soil Properties, Organic Amendment, Nutrients and SVI.

I. INTRODUCTION

Sewage sludge is a residual mixture of organic and inorganic solids derived from municipal waste water treatment. It contains large amount of major and micro nutrients besides having high organic matter content. Hence, it can improve soil physical, chemical and biological properties Singh and Agrawal (2009). Thus, it can be explored as an alternative organic source to supplement chemical fertilizers in crop production. The major interest to use this sewage sludge for growing crops is to promote the concept of wealth out of waste in order to have green and clean Earth. It also makes better earning by investing less as low cost technology.

Waste management has become a major environmental challenge, and land application of sewage sludge is generally considered the best option for disposal of sewage sludge because it offers the possibility of recycling plant nutrients, provides organic material, improves soil fertility along with physical properties and enhances crop yields (Robert *et al.*, 2011).

There is a growing concern to decrease the application of chemical fertilizer to soils using soil nutrients more efficiently and by more application of organic matter. Excessive applications of agro-chemicals in crops have adversely affected the soil flora, fauna and enzymes which help to maintain the natural fertility of soil. Higher usage of fertilizers and pesticides has also desired more irrigation causing additional stress on water sources (Yadav and Garg 2011). Incorporation of organic amendments such as animal manures, crop residues, compost and sewage sludge, to the soil, improved its properties (Mubarak *et al.* 2009; Bationo *et al.* 2006).

The organic fraction in organic amend-ments can enhance significantly soil aggregate-on, water infiltration, microbial activity, structure, and water-holding capacity particularly in soils of arid and semiarid regions and it can reduce soil compaction and erosion (Rezig *et al.* 2013; Angin and Yaganoglu 2011). Chemical properties such as cation exchange capacity, organic carbon, and soil pH may also be improved by organic amendments application (Rezig *et al.* 2013).

Application of sewage sludge can improve soil fertility and productivity (Singh and Agrawal 2008; Ahmed *et al.* 2010). Sewage sludge production has increased with urbanization throughout the world. In light of this, there is a need to increase sewage sludge safety as a soil amendment. The use of mineral fertilizer by farmers is limited because of scarcity, high costs and basic disadvantages in apparent inability to substantially redress the physical fragility and chemical deterioration of the soil (Singh and Agrawal 2007).

This necessitates research on the use of organic wastes that are cheap, readily available and environmentally friendly as fertilizers. One of the ways of improving soil fertility is by maintaining its organic matter. This is possible through the use of organic sources of fertilizer. Research has shown that organic based fertilizers are less leached into ground water than the chemical fertilizer (Sridhar, T. V. 2002).

Sludge is a concentrated suspension of solids, largely composed of organic matter, nutrients and organic solids. In addition to the major plant nutrients, sewage sludge also contains trace elements that are essential for plant growth. As soil has become deficient in certain trace elements such as Zn and Fe due to intensive cultivation, land application of sewage sludge gains importance to circumvent this problem. Seldom, it may contains toxic heavy metals. Hence, physico-chemical and chemical properties of the sewage sludge collected from Noor

Mohammed Kunta-sewage treatment plant (NMK-STP) were analysed along with nutrient status and heavy metals which are presented in the Table 1.

In India, more than 100 cities and towns have complete or partial sewerage system in addition to 700 towns with open drainage system. Sewage available from these cities and towns are estimated to about 800 million gallons day⁻¹. This amounts to an addition of organic manure to an extent of 1,456 t day⁻¹ or about 5,30,000 t annum⁻¹ with approximate nutrient content of 33,000 t N, 7,000 t P₂O₅ and 20,000 t K₂O (Sreeramulu, 2001). Because of higher nutritive value of sewage sludge, there is abundant scope in India for gainful use of this source as an organic manure to supplement chemical fertilizer in agriculture.

II. MATERIALS AND METHODS

2.1 Study site

A pot culture experiment was conducted on alfisols (red soil) at green house farm of the Department of Horticulture, College of Agriculture, Rajendranagar, Hyderabad during *kharif* 2013 to study the innovative approach of effect of sewage sludge on soil properties.

2.2 Treatments

The experiment was laid out in Completely Randomized Design (CRD) with three replications and necessary data was collected whenever required. There were seven treatments consisting of T₁ (20% sewage sludge), T₂ (40% sewage sludge), T₃ (60% sewage sludge), T₄ (80% sewage sludge), T₅ (100% sewage sludge), T₆ (RDF - Inorganic N, P and K @ 100, 100 and 100 kg ha⁻¹, respectively) and T₇ (Control).

2.3 Experimental protocol

Before starting of experiment the silent properties of soil and sewage sludge were analysed using standard methods, which are presented in the Table 1.

2.4 Soil sampling and analysis

Representative soil (Red soil) sample was analysed for its physico-chemical properties and nutrient status and the data is given in the Table 1. The pH of soil was determined in 1:2.5 soil-water suspension after half an hour equilibration, with a glass electrode pH meter (Jackson, 1973). The electrical conductivity was determined in 1:2 soil-water suspension by using conductivity bridge (Jackson, 1973) and expressed in dS m⁻¹. Organic carbon content of the soil was estimated by the wet digestion method (Walkley and Black, 1934). Available nitrogen content of the soil was estimated by alkaline permanganate method (Subbaiah and Asija, 1956). Available phosphorus was extracted from soil by using Olsen's extractant (0.5 N NaHCO₃ with pH 8.5). The readings were recorded with spectrophotometer at 420 nm and were expressed in kg P₂O₅ ha⁻¹. Available potassium was extracted from the soil using neutral normal ammonium acetate in 1:5 ratio and the readings were recorded using flame photometer. The quantity was calculated and expressed as kg K₂O ha⁻¹.

2.4.1 DTPA extractable Zinc and heavy metals in soil

Method developed by Lindsay and Norwell (1978) was used for zinc, cadmium, cobalt, nickel and lead analysis. The filtrate was used for estimation of Zn, Cd, Co, Ni and Pb using atomic absorption spectrophotometer (AAS model no. NovAA 300 BU).

2.5 Sewage Sludge Chemical Analysis

Sewage sludge used in the pot culture experiment was analyzed for physico-chemical and chemical properties by using standard procedures. The pH was determined in 1:10 sewage sludge (1 mm sieved) and water suspension by using combined glass electrode pH meter (Jackson, 1973). Electrical conductivity was determined in 1:20 sewage sludge and water suspension by using Electrical Conductivity meter (Jackson, 1973) and expressed in dS m^{-1} . Organic carbon content of sewage sludge was estimated by the wet digestion method (Walkley and Black, 1934). Nitrogen content of the sewage sludge was determined following Bremner (1965) method.

2.5.1 Digestion of Sewage Sludge for P, K and Zn

Finely ground sample (0.5 gm) was digested with 20 ml triacid mixture consisting of HNO_3 : H_2SO_4 : HClO_4 in 9:4:1. The digest was kept on the hot plate for about two hours at 160°C , until a clear digest was obtained. The intensity of yellow colour was determined by using double beam UV Spectrophotometer model UV5704SS at 420 nm (Piper, 1966). The potassium content in the triacid digest was determined by using Flame photometer model CL 361 (Jackson, 1973). Zinc in the triacid extract was determined by using the Atomic Absorption Spectrophotometer (AAS) model NOVAA300 and expressed as mg kg^{-1} (Lindsay and Norwell, 1978).

2.5.2 Digestion of sewage sludge for heavy metals (Cd, Co, Ni and Pb)

Finely ground sample (1 gm) was digested with 20 ml diacid mixture consisting of HNO_3 : HClO_4 in 9:4. The digest was kept on the hot plate for about two hours at 160°C , until a clear digest was obtained. The diacid extract was used for analysis of heavy metals (Cd, Co, Ni and Pb) using the Atomic Absorption Spectrophotometer (AAS) model NOVAA300 and expressed as mg kg^{-1} (Swarajya *et al.*, 2010).

Table1. Initial Properties Of Soil And Sewage Sludge

Parameters	Units	Values	
		Soil	Sewage Sludge
Physio-chemical properties			
Soil reaction	pH	7.79	5.81
EC	dS m ⁻¹	0.88	5.48
OC	%	0.72	25.76
Total major nutrient status			
Nitrogen	Kg ha ⁻¹	271.64	3.29(%)
Phosphorus	Kg P ₂ O ₅ ha ⁻¹	38.75	1.23(%)
Potassium	Kg K ₂ O ha ⁻¹	253.81	2.98(%)
Micro nutriente			
Zinc	mg kg ⁻¹	3.61	27.72
Total heavy metals			
Cadmium	mg kg ⁻¹	0.23	0.97
Cobalt	mg kg ⁻¹	0.13	0.37
Nickel	mg kg ⁻¹	0.83	1.69
Lead	mg kg ⁻¹	3.85	6.86
SVI	mL g ⁻¹	-	482.71

2.5.3 Sludge volume index (SVI)

The sludge volume index is the volume in milliliters occupied by one gram of a suspension after 30 minutes settling (Dick and Vesilind, 1969). SVI determined through used standard laboratory test method (Davis *et al.*, 2008). The procedure involves measuring the Mixed Liquor Suspended Solids (MLSS) value and also the sludge settling rate.

$$SVI (mL g^{-1}) = \frac{SSV (mL L^{-1})}{MISS (mg L^{-1})} \times 1000$$

2.6 Statistical Analysis

The results of pot culture study were subjected to statistical analysis as per the procedures outlined by Snedecor and Cochran (1967).

III. RESULTS AND DISCUSSION

3.1 Physico-chemical properties of sewage sludge

The sewage sludge was moderately acidic with pH of 5.81. It was slightly saline with EC value of 5.48 dS m⁻¹. Organic carbon was high (27.76%) and SVI was 482.71 mL g⁻¹. The available total nutrients viz., N, P and K in sewage sludge were 3.29, 1.23 and 2.98%, respectively. The N, P and K content of sewage sludge was more by 6.58, 6.15 and 5.96 times, respectively than Farm Yard Manure and compared with urban compost, available N, P and K was more by 6.58, 2.46 and 2.98 times, respectively. The triacid extractable zinc of sewage sludge was 27.72 mg kg⁻¹ which was within the maximum permissible limits as per USEPA standards, 1993.

3.1.1 Diacid extractable heavy metals (Cd, Ni, Co and Pb)

The diacid extractable contents of heavy metals Cd, Ni, Co and Pb were 0.97, 1.69, 0.37 and 6.86 mg kg⁻¹, respectively. The heavy metal contents were within the maximum permissible limits. (USEPA standards 1993 and Water Research Commission 1997).

3.2 Physico-chemical properties of soil

The soil was slightly alkaline with pH of 7.79. Its EC value was 0.88 dS m⁻¹. Organic carbon was high (0.72%). The available total nutrients viz., N, P and K in soil were 271.6, 38.7 and 253.8 kg ha⁻¹, respectively. The triacid extractable zinc of soil was 3.6 mg kg⁻¹.

3.2.1 Diacid extractable heavy metals (Cd, Ni, Co and Pb)

The diacid extractable contents of heavy metals Cd, Ni, Co and Pb were 0.23, 0.83, 0.13 and 3.85 mg kg⁻¹, respectively. The heavy metal contents were within the maximum permissible limits. (USEPA standards 1993 and Water Research Commission 1997).

3.3 Effect of Sewage Sludge on Soil Properties

The analysis of soil, collected from marigold experiment at initial (before transplanting), mid (45 DAT) and harvesting stages (90 DAT) was carried to assess the effect of sewage sludge on soil properties.

3.3.1 Soil reaction (pH)

The soil pHs recorded at initial, mid and harvesting stages are presented. The soil pH differed significantly at all the stages by different treatments of sewage sludge. The pH of soil increased as crop age advanced. Significantly lowest soil pH (5.81) was recorded at initial stage in T₅ followed by T₄ (6.49). In contrast, highest pH of 7.79 was observed in T₇. The soil pH in T₅ was significantly less by 34.08%, 23.41% and 11.70%, respectively as compared with T₇, T₆ and T₄. The soil pH at mid stage ranged from 6.16 in T₅ to 7.90 in T₇. The pH recorded in T₅ was significantly less by 28.25%, 16.88% and 10.23%, respectively as compared with T₇, T₆ and T₄. The pH observed in T₁, T₂ and T₃ were on par with each other. Similar trend in soil pH that observed at initial and mid stage was noticed even at harvesting stage. The lowest soil pH (6.53) was obtained in T₅ and the highest pH of 8.03 was observed in T₇ as compared with other treatments. The pH was 22.97% less in T₅ than T₇. Soil pH was though slightly alkaline initially, changed to neutrality with increase in dose of sewage sludge

application and with advancement in crop age. Thus, in T₅ at harvesting stage, the pH was found to be neutral (6.53). The observation of lowest soil pH in T₅ at initial, mid and also at harvesting stages can be attributed to more acidic nature of sewage sludge and the quantity of sewage sludge applied in this treatment was more as compared with rest of the treatments. This finding can be corroborated by the observations made by Moreno *et al.* (1997) that release of humic acid due to biodegradation of organic carbon rich sewage sludge. Jingjun Su and Phunch (2007) also stated that, pH was lower in surface soil with the application of more sewage sludge than control. Soil pH decreased significantly from 6.36 to 6.01 by the addition of organic manures like cow dung. Reduction in soil pH with application of poultry manure and mustard oil cake was also reported by Ullah *et al.* (2008). Similar result was also expressed by Singh and Agrawal (2010) who reported that, with increased dose of sewage sludge application, soil pH decreased as compared with control.

3.3.2 Electrical Conductivity (EC)- The highest EC (5.48 dS m⁻¹) was observed in T₅ followed by T₄ and T₃. The lowest EC of 0.88 dS m⁻¹ was observed in T₇. The soil EC was recorded more by 30.48% in T₅ than T₄. The soil EC recorded at mid stage ranged from 0.76 dS m⁻¹ in T₇ to 5.25 dS m⁻¹ in T₅. The EC recorded in T₅ was significantly more by 37.08% and 108.33%, respectively as compared with T₄ and T₃, similar that seen at initial stage. The EC obtained in T₃ was significantly more than T₂. At harvesting stage, the highest soil EC (4.89 dS m⁻¹) was recorded in T₅ and was significantly more than T₄ (3.53 dS m⁻¹) followed by T₃ (2.37 dS m⁻¹). The lowest soil EC of 0.75 dS m⁻¹ was observed in T₇. The soil EC was more by 38.53% in T₅ than T₄. Similar trend was also observed at initial and mid stage. Soil EC at initial stage was though slightly saline and it was also slightly saline in T₅ at harvesting stage. The higher soil EC recorded at initial, mid and harvesting stages in T₅ may be due to higher salt content and mineralization of sewage sludge. Mallesh (2009) also stated that, there was an increase in EC of the soil from 0.38 to 0.53 dS m⁻¹ with the application of compost, from 0.38 to 0.45 dS m⁻¹. The application of farm yard manure and poultry manure also resulted similarly (Saruhan *et al.*, 2010). Singh and Agrawal (2010) also opined that, there was increase in soil EC with increase in dose of sewage sludge application.

3.3.3 Organic Carbon (OC) content- The content of soil organic carbon was increased as crop age advanced. The soil organic carbon (SOC) recorded at initial stage in T₅ was highest (25.76%) followed by T₄ (21.65%). The lowest SOC of 0.72% was observed in T₇. The soil organic carbon was significantly more by 18.98% in T₅ than T₄. The content of soil organic carbon at mid stage ranged from 0.71% in T₇ to 27.86% in T₅. In T₅, it was significantly more to the extent of 20.35%, 51.33% and 121.11%, respectively as compared with T₄, T₃ and T₂, similar to that seen at initial stage. The SOC notice in T₆ and T₇ were on par with each other. The trend observed in soil organic carbon at harvesting stage was similar to initial and mid stages. Significantly highest (32.56%) and lowest soil organic carbon (0.69%) were recorded in T₅ and T₇, respectively. Soil organic carbon at initial stage was medium and was high at harvesting stage in T₅. The highest soil organic carbon recorded at initial, mid and harvesting stages in T₅ was due to higher organic carbon, organic matter and nutritional value of sewage sludge. Similar result was expressed by Reddy *et al.* (2001) and according to them application of sewage sludge and urban compost in 1:1 ratio resulted in high organic carbon content. Poornesh *et al.* (2004) also stated that, the application of urban garbage compost increased the organic carbon content in soil. The macronutrients in the sewage sludge serve as a good source of organic matter and plant nutrients (Singh and Agrawal, 2008).

Similar results were also expressed by Begum (2011) that the organic carbon increased from 2.4 to 3.3 g kg⁻¹ with increase in dose of municipal sewage sludge vermicompost application from 10 to 30 t ha⁻¹ at Bengaluru.

3.3.4 Available Nitrogen (kg ha⁻¹)- The availability of nitrogen increased with increase in dose of sewage sludge and with advancement in crop age. The highest soil nitrogen content (562.4) was observed at initial stage in T₅ followed by T₄ (552.9) and T₃ (482.6), unlike soil organic carbon where, T₅ recorded significantly highest as compared with T₄. The lowest nitrogen (271.6) was observed in T₇ followed by T₁ (265.4). Available soil nitrogen at mid stage ranged from 252.8 in T₇ to 608.4 in T₅. In T₅, it was significantly more by 4.20% than T₄, unlike that noticed at initial stage. The available nitrogen in T₂ was significantly more by 25.71% than T₁. The data recorded on available nitrogen at harvesting stage in T₅ was significantly highest (678.2) and it was more by 9.13% and 25.56%, respectively as compared with T₄ and T₃. Similar trend was also noticed at mid stage. The lowest available nitrogen (248.9) was observed in T₇ followed by T₁ (275.9). Available soil nitrogen content in T₅ at both initial stage and harvesting stage can be categorized as high. Highest available nitrogen in T₅ at initial, mid and harvesting stages was due to more nitrogen content of sewage sludge and its availability with more sewage sludge application. Relatively high per cent of organic carbon in sewage sludge increased the cation exchange capacity, which helped to retain essential plant nutrients within the rooting zone due to additional cation binding sites (Soon, 1981). Similar trend was also observed by Singh and Agrawal (2010).

3.3.4 Available Phosphorous (kg P₂O₅ ha⁻¹)- The highest phosphorus content (59.5) at initial stage recorded in T₅ was differed significantly as compared with rest of the treatments. This trend was also observed in soil organic carbon. The availability of P ranged from 38.7 in T₇ to 59.5 in T₅. The increase in available phosphorus was more by 11.21% in T₅ than T₄. Highest available phosphorus (64.2) at mid stage was recorded in T₅ and it was significantly more than that in T₄ (59.9) followed by T₃ (52.6), similar that observed at initial stage. The lowest available phosphorus (36.3) was observed in T₇. The available phosphorus was more by 7.18% in T₅ than T₄. The trend observed in available phosphorus at harvesting stage was similar to initial and mid stages. Significantly highest (52.7) and lowest available phosphorus (31.9) were obtained in treatments of T₅ and T₇, respectively. Soil phosphorus content at initial and harvesting stage was high in T₅. More available phosphorus in T₅ at initial, mid and harvesting stages as compared with rest of the treatments can be attributed to higher phosphorus availability from sewage sludge similar to nitrogen. This finding can be supported by the observation made by Singh and Agrawal (2010) that, the soil P content increased with increase in dose of sewage sludge. Soon (1981) also stated that, relatively high per cent of organic carbon in sewage sludge increased the cation exchange capacity, which subsequently helped to retain essential plant nutrients within the rooting zone.

3.3.5 Available Potassium (kg K₂O ha⁻¹)

Highest available soil potassium (618.3) at initial stage was recorded in T₅ followed by T₄ (570.1) and T₃ (497.4), similar to trend of available nitrogen. The available potassium was more by 8.45% in T₅ than T₄. The lowest available potassium (253.8) was recorded in T₇. The data recorded on soil available potassium at mid stage ranged from 243.6 in T₇ to 643.2 in T₅. The available potassium recorded in T₅ was significantly more by 9.00%, 25.77% and 90.35%, respectively as compared with T₄, T₃ and T₂, unlike to the trend observed at initial stage among the T₅, T₄ and T₃. Similar trend in soil available potassium that observed at initial and mid was also

noticed even at harvesting stage. The lowest soil available potassium (238.1) was obtained in T₇ and the highest available potassium of 662.6 was observed in T₅ as compared with other treatments. The available potassium was 9.39% more in T₅ than T₄. Similar result was also expressed by Saruhan *et al.* (2010) that, the availability of K in soil increased (528.6, 688.4 and 789.1 mg kg⁻¹, respectively) with the increase in sewage sludge application rates (@ 3, 6 and 9 t ha⁻¹, respectively). The explanation given in case of more organic carbon, nitrogen and phosphorus also holds good here in terms of more availability of potassium in T₅ than T₇.

3.3.6 DTPA extractable Zinc (mg kg⁻¹)

Significant differences were observed at initial stage due to the different rates of sewage sludge application. The highest DTPA extractable zinc (27.72) was observed in T₅ followed by T₄ and T₃. The lowest DTPA extractable zinc of 3.61 was observed in T₇. The soil DTPA extractable zinc was more by 21.37% in T₅ than T₄. This trend was similar that seen in case of nitrogen and potassium availability at initial stage. Significantly highest DTPA extractable zinc (30.44) at mid stage was recorded in T₅ followed by T₄ (23.22), unlike that at initial stage among T₅ and T₄. The lowest DTPA extractable zinc (3.49) was observed in T₇. The zinc content was significantly more by 31.09% in T₅ than T₄. DTPA extractable zinc of soil at harvesting stage ranged from 3.56 in T₇ to 31.60 in T₅. In T₅ it was significantly more by 26.00% than T₄, similar to that noticed at mid stage. The lowest DTPA extractable zinc (3.56) was recorded in T₇ followed by T₁ (8.65) and T₂ (11.79). Studies on sewage sludge by Adams and Sanders (1984) showed that, metal concentration released to the supernatant liquid increased as pH decreased below the threshold value, which was 5.8 for Zn in loaded sludge. The results expressed by Singh and Agrawal (2008 and 2010) and Begum (2011) corroborates this finding of the present study that in T₅, pH was significantly lowest as compared with rest of treatments resulting in release of Zn to soil.

3.3.7 DTPA extractable Lead (mg kg⁻¹)

The highest DTPA extractable Pb (6.863) was observed in T₅ followed by T₄ (6.623) and T₃ (6.567). The lowest DTPA extractable Pb of 3.854 mg kg⁻¹ was observed in T₇. The Pb recorded was more by 78.07% in T₅ than T₇. This trend was similar that observed in case of potassium and zinc availability at initial stage. The DTPA extractable Pb recorded at mid stage ranged from 3.852 in T₇ to 10.443 in T₅. The Pb recorded in T₅ was significantly more by 15.38% than T₄. Extractable Pb in T₃ (8.259) was also significantly more than T₂ (7.290). The trend of DTPA extractable Pb in soil at harvesting stage ranged from 3.972 in T₇ to 14.941 in T₅. The highest DTPA extractable lead (14.941) was recorded in T₅ followed by T₄ and T₃. The DTPA extractable Pb was significantly more by 8.76% in T₅ than T₄. This trend was similar that at mid stage. The magnitude of increase in DTPA Pb content in T₅ compared to T₄ was much lower at mid stage (15.38%) and lowest (8.76%) at harvesting stage than at initial stage (78.07%). The DTPA extractable Pb content was within the maximum permissible limits as per WHO standards, 1996. More availability of DTPA extractable Pb in T₅ as compared with rest of the treatments can be attributed to low pH in this treatment. The present experimental results follow the observations made by Singh and Agrawal (2010) that with increase in dose of sewage sludge application, soil Pb content increased. Begum (2011) also reported higher availability of heavy metals and zinc with municipal sewage sludge vermicompost.

3.3.8 DTPA extractable Nickel (mg kg^{-1})

The DTPA extractable nickel increased in soil with advancement in crop age. DTPA extractable Ni at initial stage ranged from lowest value of 0.830 in T₇ to highest value of 1.693 in T₅. In T₅, it was significantly more by 36.86% and 69.13%, respectively as compared with T₄ and T₃. This trend was similar to that observed in case of K, Zn and Pb availability at initial stage. The Ni content in T₁ 0.841 and in T₂ (0.912). T₆ (0.886) and T₇ (0.830) were on par with each other in Ni content. The DTPA extractable Ni in soil recorded at mid stage ranged from 0.826 in T₇ to 1.860 in T₅. The DTPA extractable Ni was more by 36.97% and 83.79%, respectively as compared with T₄ and T₃, which was similar to that recorded at initial stage. The highest DTPA extractable Ni content (2.233) recorded at harvesting stage was observed in T₅ followed by T₄. The lowest DTPA extractable Ni (0.813) was observed in T₇. The Ni content was more by 55.39% in T₅ than T₄, similar to that seen at initial and mid stage. The data recorded on Ni content was within the maximum permissible limits as per WHO standards, 1996. Higher DTPA extractable nickel (Ni) in T₅ was found due to more concentration in sewage sludge and Ni availability from sewage sludge due to low pH. Studies on sewage sludges done by Adams and Sanders (1984) showed that, metal concentration released into the supernatant liquid increased as pH decreased.

3.3.9 DTPA extractable Cobalt (mg kg^{-1})

Significantly highest DTPA extractable cobalt (0.373) was recorded at initial stage in T₅ followed by T₄ (0.341) and T₃ (0.262). Similar trend was also observed in case of K, Zn, Pb and Ni content at initial stage. Significantly lowest DTPA extractable cobalt (0.136) was observed in T₇ followed by T₁ (0.185). The DTPA extractable cobalt at mid stage ranged from 0.140 in T₇ to 0.459 in T₅. The cobalt content was significantly more by 31.90% in T₅ than T₄, similar to that recorded at initial stage. The cobalt content recorded in T₁ and T₆ was on par with each other. The highest DTPA extractable cobalt content (0.680) in soil at harvesting stage was observed in T₅ followed by T₄ (0.414). The lowest cobalt content (0.145) was observed in T₇ followed by T₁ (0.198). This trend was unlike to the trend that noticed at initial and mid stage among T₇ and T₁. Generally sewage sludge consists of organic compounds, macronutrients and a wide range of micronutrients, non-essential trace metals, organic micro pollutants and microorganisms (Kulling *et al.*, 2001). The present result was also similar to the observation made by Singh and Agrawal (2007). Similar result was also expressed by Saruhan *et al.* (2010) that, the concentration of cobalt in soil increased with increase in sewage sludge application rates.

3.3.10 DTPA extractable Cadmium (mg kg^{-1})

The DTPA extractable cadmium increased in soil as the crop age advanced. Significantly highest DTPA extractable Cd (0.975) in soil was recorded at initial stage in T₅ followed by T₄ (0.619) and T₃ (0.556) similar to other heavy metals *viz.*, Ni, Co etc. The lowest DTPA extractable cadmium (0.234) was found in T₇ followed by T₁ (0.492). Extractable cadmium content at mid stage ranged from 0.237 in T₇ to 1.145 in T₅. In T₅, it was significantly more by 15.19% than T₄, similar to that seen at initial stage. The DTPA extractable cadmium (0.568) in T₂ was on par with T₁ (0.568). Extractable Cd content in soil at harvesting stage was significantly highest (1.363) in T₅ followed by T₄ (1.199) and T₃ (0.680). The Cd content was more by 13.68% in T₅ than T₄. Cadmium content at all stages of observation was within the maximum permissible limits as per WHO standards (1996).

3.3.11 Potting mixture temperature (°C)

The temperature values were recorded at both the 45 and 60 DAT. Potting mixture temperature at 45 DAT ranged from 32.7°C in T₇ to 35.7°C in T₅. In T₁ (33.0°C), T₂ (33.2°C), T₃ (33.5°C), T₆ (32.9°C) and T₇ (32.7°C), the temperatures were on par with each other. The temperature was significantly more by 9.17% in T₅ than T₇. The highest temperature (35.8°C) of potting mixture measured at 60 DAT in T₅ followed by T₄ (35.2°C), similar to that noticed at 45 DAT. The lowest temperature of 31.7°C was observed in T₇ followed by T₁ (32.3°C). The higher temperatures of potting mixture recorded at 45 and 60 DAT in T₅ may be due to more decomposition and higher root concentration in higher dose of sewage sludge treatment as compared with lower dose of sewage sludge. Miller (1974) reported that, soil temperature was the major factor influencing the rate of sewage sludge decomposition. He demonstrated a relationship between the amounts of CO₂ evolved and degree temperature at Polytechnic Institute of Virginia. The rate of decomposition increased when the amount of sewage sludge increased (Sommers *et al.*, 1979). The rate of sludge decomposition in soil was influenced by temperature, type and amount of sludge and time of application (Tester *et al.*, 1979). The mineralization rate of sewage sludge in soil increased approximately 1.9 times when the temperature was increased from 8 to 22°C (Hsieh *et al.*, 1981).

IV. SUMMARY AND CONCLUSIONS

4.1 Summary

Sewage Sludge

The physico-chemical and chemical characteristics of sewage sludge were done which indicated that it was moderately acidic (pH 5.81). EC was 5.48 dS m⁻¹ and total organic carbon was 25.76 per cent. Total N, P and K contents of sewage sludge were 3.29, 1.23 and 2.98 %, respectively. The triacid extractable zinc, in sewage sludge was 27.72 mg kg⁻¹. The diacid extractable heavy metals *viz.*, cadmium, cobalt, nickel and lead were accordingly 0.97, 0.37, 1.69 and 6.86 mg kg⁻¹. All the heavy metals were within maximum permissible limits (USEPA standards) The SVI was 482.71 mL g⁻¹.

Soil- The soil was slightly alkaline with pH of 7.79. Its EC value was 0.88 dS m⁻¹. Organic carbon was high (0.72%). The available total nutrients *viz.*, N, P and K in soil were 271.6, 38.7 and 253.8 kg ha⁻¹, respectively. The triacid extractable zinc of soil was 3.6 mg kg⁻¹. The diacid extractable contents of heavy metals Cd, Ni, Co and Pb were 0.23, 0.83, 0.13 and 3.85 mg kg⁻¹, respectively. The heavy metal contents were within the maximum permissible limits.

Effects on Soil properties

Application of sewage sludge increased the pH of soil with advancement in crop age in all the treatments. The pH among the treatments of T₅ to T₇ varied from 5.81 to 7.79 at initial stage, 6.16 to 7.90 at mid stage and was 6.53 to 8.03 at harvesting stage. Similar trend was also observed even in case of soil organic carbon content, which ranged from 25.76% in T₅ to 0.72% in T₇ at initial stage. It ranged from 27.86 to 1.25% at mid stage and 32.56 to 0.69% at harvesting stage in the same treatments of, respectively T₅ and T₇. Significantly highest EC of 5.48 dS m⁻¹ was recorded in T₅ followed by T₄ (4.20 dS m⁻¹) at initial stage. In contrast, the lowest EC (0.88 dS m⁻¹) was recorded in T₇. The trend was similar even at mid and harvesting stages. The percentage of increase in

T₅ was significantly highest by 172.42, 108.15% and 178.29% respectively, in terms of soil available nitrogen, phosphorus and potassium accordingly as compared with T₇ at harvesting stage. This trend of N, P and K availability was similar to trend of SOC content. The available nitrogen, phosphorus and potassium content in soil exhibited high rating at all the stages of observation. DTPA extractable zinc was ranged from T₇ to T₅, 3.61 to 27.72 mg kg⁻¹ at initial stage, 3.49 to 30.44 mg kg⁻¹ at mid stage and 3.56 to 31.60 mg kg⁻¹ at harvesting stage. The DTPA extractable heavy metals viz., Pb, Ni, Co and Cd of soil in respect of different sewage sludge treatments elicited significant increase with increase in sewage sludge application rates and also increased with advancement in crop age. The Pb was ranged from 3.972 to 14.941 mg kg⁻¹, Ni was 0.813 to 2.233 mg kg⁻¹, Co was 0.145 to 0.680 mg kg⁻¹ and Cd was 0.239 to 1.363 mg kg⁻¹ at harvesting stage, accordingly in Control (least) and 100% sewage sludge treatment (highest). The trend of heavy metals availability was similar to trend of SOC, EC, N, P, K and Zn availability. The heavy metals viz., Pb, Ni, Co and Cd content in soil at initial, mid and harvesting stages were within the maximum permissible limits. The data of potting mixture temperature was recorded at the depth of 15 cm with soil thermometer in both marigold and golden rod. The temperature increased significantly with increase in sewage sludge application rates. The maximum temperature (35.7°C at 45 DAT and 35.8°C at 60 DAT) was observed in T₅. In contrast, the minimum temperature (32.7°C at 45 DAT and 31.7°C at 60 DAT) was observed in Control.

V. CONCLUSIONS

(1) The NPK content of sewage sludge used in the present experiment was high along with organic carbon content. The content of heavy metals Pb, Ni, Co and Cd was within maximum permissible limits. (2) The major nutrients (NPK), organic carbon, micronutrient (Zn) and heavy metals (Pb, Ni, Co and Cd) content in soil were found to be highest in the treatment of 100% sewage sludge (T₅) at all stages of observation. However, the heavy metals (Pb, Ni, Co and Cd) were within maximum permissible limits as per USEPA standards.

VI. FUTURE SCOPE OF WORK

Thus, sewage sludge generated from NMK-STP located near College of Agriculture was found to be a good organic source of fertilizer in eco-friendly way. However, the trial needs further study to confirm the results before extensive and intensive use of sewage sludge in the field.

Author's Contribution

The research is financially supported by the ANGRAU, Hyderabad. The authors are grateful to the technicians of the laboratory of the department of Environment Sciences, for their help and encouragement during analysis. Dr. Baby Akula is the Professor who originated the scientific concept, designed the work, supervised and guided all the different components of this work. Dr. Harish kumar sharma was responsible for data collection, interpreted results and wrote the manuscript including analysis of results. Jagdishwar Reddy was responsible for sewage sludge collection, analysis and presentation of results.

REFERENCES

- [1]. Adams, T. M. and Sanders, J. R. (1984). "The effect of pH on the release to solution of zinc, copper and nickel from metal loaded sewage sludges". *Env. Poll.. (Series B)* 8: 85-99.
- [2]. Angin, I. and Yaganoglu. (2011). "Effects of sewage sludge application on some physical and chemical properties of a soil affected by wind erosion". *J Agri Sci Tech.* 13:757-768.
- [3]. Bationo, A., Kihara, J., Vanlauwe, B., Waswa, B. and Kimetu, J. (2006). "Soil organic carbon dynamics, functions and management in West African agro-ecosystems". *Agric Syst.* 94:13-25.
- [4]. Begum, A. (2011). "Evaluation on municipal sewage sludge vermicompost on two cultivars of tomato (*Lycopersicon esculentum* L.) plants". *Inter. Journal of Chemical Technology Research.* 3 (3): 1184-1188.
- [5]. Bremner, J. M. (1965). "Total nitrogen. In: *Methods of Analysis, Part-II* (C A Black, ed.)". American Society of Agronomy, Madison, Wisconsin, USA. 1149-1176.
- [6]. Davis, Mackenzie Leo and David, A. (2008). "Cornwell". *Introduction to Environmental engineering.* Dubuque, IA: McGraw-Hill Companies, 2008. Print.
- [7]. Dick, R. I. and P. A. Vesilind. (1969). "The SVI - What is it? *Journal of Water Pollution Control Fed.* 41: 1285.
- [8]. Hsieh, Y. P., L. A. Douglas. and L. H. Motto. (1981). "Modeling Sewage Sludge Decomposition in Soil: I. Organic Carbon Transformation". *J. of Env. Qua.* 10: 54-59.
- [9]. Ahmed, Hassan. A. Fawy. and E. S. Abdel-Hady. (2010). "Study of sewage sludge use in agriculture and its effect on plant and soil". *Agriculture and Biology Journal of North America.* 1 (5): 1044-1049.
- [10]. Jackson, M. L. (1973). "Soil Chemical Analysis". Oxford IBH Publi. House, Bombay. 38-39.
- [11]. Jingjun, Su. And Phunch, S. (2007). "Fractionation and Mobility of Phosphorus in a Sandy Forest Soil Amended with Biosolids". *Env Sci. Pol. Res.*14 (7): 529-535.
- [12]. Kulling, D. Stadelmann, F. and Herter, U. (2001). "Sewage Sludge – Fertilizer or Waste? UKWIR Conference, Brussels.
- [13]. Lindsay, W. L. and Norwell, W. A. (1978). "Development of DTPA soil test for zinc, iron, manganese and copper". *Soil Science Society of American Journal.* 43: 421-428.
- [14]. Mallesh, B. (2009). "Studies on impact of enriched microbial (EM) compost application on paddy and maize". M. Sc Thesis. Acharya N. G. Ranga Agri. University, Hyderabad.
- [15]. Miller, R. H. (1974). "Factors Affecting the Decomposition of an Anaerobically Digested Sewage Sludge in Soil". *Journal of Environmental Quality.* 3: 376-380.
- [16]. Moreno, J. L., Garcia, C., Hernandez, T. and Ayuso, M. (1997). "Application of comp-osted sewage sludges contaminated with heavy metals to an agricultural soil: effect on lettuce growth". *So. Sci. Pl. Nutr.* 4: 565-573.
- [17]. Mubarak, A. R., Ragab, O. E., Ali, A. A. and Hamed, N .E. (2009). "Short-term studies on use of organic amendments for amelioration of a sandy soil". *Afr J Agr Res.* 4(7):621-627.
- [18]. Piper, C. S. (1966). *Soil and Plant Analysis.* Hans Publications, Bombay. 59.

- [19]. Poornesh, A. S., Reddy, V. C. and Murthy, K. N. K. (2004). "Effect of urban garbage compost and sewage sludge on yield of ragi". *Environment and Ecology*. 22 (3): 720-723.
- [20]. Reddy, V. C., Yogananda, S. B., Gowda, A. P. M., C. . S., Babu, B. T. R. and Raghavendra. (2001). "Influence of urban compost and sewage sludge on growth and yield of bhendi". *South Ind. Hort.*49: 151-154.
- [21]. Rezig, FAM, Mubarak, A. R. and Elhadi, E. A. (2013). "Impact of organic residues and mineral fertilizer application on soil-crop system: II soil attributes". *Arch Agron Soil Sci*. 9:1245–1261.
- [22]. Robert, Edwin White, Silvana, I. Torri. and Rodrigo, Studart, Correa. (2011). "Biosolids Soil Application": Agronomic and Environmental Implications. Hindawi Publishing Corporation. Applied and Environmental Soil Science. Volume 2011, Article ID 928973, 3 pages doi:10.1155/2011/928973.
- [23]. Saruhan, Veysel, Ismail, Gul. and Isil Aydin. (2010). "The effects of sewage sludge used as fertilizer on agronomic and chemical features of bird's foot trefoil (*Lotus corniculatus* L.) and soil pollution". *Scientific Research and Essays*. 5 (17): 2567-2573.
- [24]. Singh, R. P. and Agrawal, M. (2007). "Effects of sewage sludge amendment on heavy metal accumulation and consequent responses of *Beta vulgaris* plants". *Chemo*. 67: 2229-2240.
- [25]. Singh, R. P. and Agrawal, M. (2008). "Potential benefits and risks of land application of sewage sludge". *Waste Mana*. 28: 347-358.
- [26]. Singh, R. P. and Agrawal, M. (2009). "Use of sewage sludge as fertilizer supplement for *Abelmoschus esculentus* plants: physiol-ogical, biochemical and growth responses". *Inter. J. Env. Waste Management*. 3: 91-106.
- [27]. Singh, R. P. and Agrawal, M. (2010). "Effect of different sewage sludge applications on growth and yield of *Vigna radiata* L. field crop: Metal uptake by plant". *Ecological Engineering*. 36: 969-972.
- [28]. Snedecor, G. W. and Cochran, W. G. (1967). "Statistical methods. 6th Edition, Iowa state University Soil Analysis". Arner Society Agronomy Publisher.
- [29]. Sommers, L. E., D. W. Nelson. and D. J. Silviera. (1979). "Transformations of Carbon, Nitrogen and Metals in Soils Treated with Waste Materials". *J Env Quality*. 8: 287-294.
- [30]. Soon, Y. K. (1981). "Solubility and sorption of cadmium in soils amended with sewage sludge". *Journal of Soil Science*. 32: 85-95.
- [31]. Sreeramulu, U. S. (2001). "Reuse of municipal sewage and sludge in Agriculture". Scientific Publishers (India), Jodhpur.
- [32]. Subbaiah, B. V. and Asija, C. L. (1956). "A rapid procedure for the estimation of available nitrogen in soils". *Cur Sci*. 25: 32.
- [33]. Swarajya, G., Prabhu Prasadini, P., Ramesh Thatikunta and VNLV Tayaru. (2010). "Environmental Science. A Practical Manual, BS publications, Hyderabad.
- [34]. Tester, C. F., L. J. Sikora, J. M. Taylor. and J. F. Parr. (1979). "Decomposition of Sewage Sludge Compost in Soil: III. Carbon, Nitrogen and Phosphorus Transformations in Different Sized Fractions". *Journal of Environmental Quality*. 8: 79-82.
- [35]. Ullah, M. S., Islam, M. S., Islam, M. A. and Haque, T. (2008). "Effects of organic manures and chemical fertilizers on the yield of brinjal and soil properties". *J of Bangladesh Agri. University*. 6 (2): 271-276.

- [36]. USEPA. (1993). "Clean Water Act, sec. 503, vol. 58, no. 32". (United State Environmental Protection Agency Washington, D.C.).
- [37]. Walkley, A. J and Black, C. A. (1934). "An examination of different methods for determining soil organic matter and a proposed modification of the chromic acid titration method". Soil Science. 37: 29-38.
- [38]. Water Research Commission. (1997). "Permissible Utilisation and Disposal of Sewage Sludge". Water Research Commission P O Box 824 Pretoria 1: 1-83.
- [39]. WHO. (1996). "Permissible limits of heavy metals in soil and plants". (Genava : World Health Organization), Switzerland. 2 (1):1-9.
- [40]. Yadav, A. and Garg, V. K. (2011). "Recycling of organic wastes by employing *Eisenia fetida*". Bioresour Technol. 102:2874-2880.