## International Journal of Advanced Technology in Engineering and Science Vol. No.3, Special Issue No. 01, September 2015

www.ijates.com

ijates SSN 2348 - 7550

# STUDY OF POLLUTION STATUS IN RIVER GANGA AT GOLA GHAT AND PERMUT GHAT IN 2013 IN KANPUR IN UTTAR PRADESH

R.C. Verma<sup>1</sup>, Om Kumari<sup>2</sup>, Sangeeta Awasthi<sup>3</sup>

<sup>1</sup>Deptt.of Chemistry, Janta P.G. College, Bakewar, Etawah (India) <sup>2</sup>Deptt.of Chemistry, K.K.P.G. College, Etawah (India) <sup>3</sup>Deptt.of Zoology, A.N.D. Colleg, Kanpur (India)

#### **ABSTRACT**

Water samples from river Ganga at Gola Ghat and Permut Ghat in Kanpur in Uttar Pradesh were collected and phyco-chemical parameters were determined using standard analytical procedure in Jan.to Dec.2013.pH (7.9-9.3), chloride and phosphate contents of water samples were determined 15-25 mg/l and 0.05-0.16 ppm respectively. Total hardness 94.6-166.1 mg/l, fluoride level also 6.0-6.3 mg/l, DO of samples were 4.2-7.4 mg/l, BOD were 3.0-7.5 mg/l and COD were 25-40 mg/l. These results were said to their agreed with the limits set by World Health Orgnization (WHO) for drinking water.

Keyword: Pollution Status, WHO, Drinking Water.

#### I. INTRODUCTION

Water the most essential requisites that nature has provided to sustain life on earth. About 80% earth surface is covered by water. The deteriorate quality of water create various problems for mankind. The growth in population, about 90% of which occur in urbon area, increases the demand for water for domestic and industrial uses. Water pollution from domestic and human waste is the main cause for human being water born desease. The industrial water pollution is due to inadequate measure adopted in the industry for the abatement of pollution. It is need of time to protect environment for present and future generations. The purpose of study into prepares qualitative assessment of abiotic and biotic conditions prevailing in river Ganga.

#### II. MATERIAL AND METHOD

The Kanpur on National Highway no.1 and 2 falls on Broad Gauge NR Railway line between Delhi and Kolkata.

Water samples were collected in clean polythene bags and subjected to chemical analysis for measurement of different parameters such as temperature, pH, DO, BOD, COD, fluoride, chloride, phosphate, hardness and total dissolved by standered analytical methods in Jan. to Dec.2013.

### International Journal of Advanced Technology in Engineering and Science Vol. No.3, Special Issue No. 01, September 2015

www.ijates.com

#### III. RESULT AND DISCUSSION

ijates

ISSN 2348 - 7550

The values of different parameter with respect to sampling stations (Gola Ghat and Permut Ghat) are given in Table-1 and Table-2. The transparency values of samles were 19.5-54.5 cm. Maximum value is 54.5 in Jan. 2013 at Permut Ghat while minimum value is 19.5 in Jun.2013 at Gola Ghat. The temperature of water was 16.2-36.4 °C. Maximum value is 36.4 in Jun.2013 at Gola Ghat while miminum is 16.2 in Jan.2013 at Permut Ghat. The WHO(1992) did not recommend any definite temperature for drinking water. The pH value were 7.9-9.3. Maximum value is 9.3 at Jan.2013 at Gola Ghat while minimum value is 7.9 in May,2013 at Permut Ghat. Total dissolved were 135-140 mg/l. Maximum value is 140 mg/l in Jul.2013 at Permut Ghat while minimum value is 135 mg/l in Jan & Feb.2013 at Permut Ghat, which are under limits. The total hardness of water were 94.6-166.1 mg/l. maximum value is 166.1 in Jun.2013 at Gola Ghat while minimum value is 94.6 in Oct.2013 at Permut ghat. The levels of hardness are below the level (300 mg/l) as laid down by Indian standard and thus water is soft. Fluoride level were 6.0-6.3 mg/l. The maximum value is 6.3 in Jul.2013 at Gola Ghat & in June & July 2013 at Permut Ghat while minimum value is 6.0 in May, 2013 at Gola Ghat and in Apr. 2013 at Permut Ghat, which are low. The chloride contents were 15-25 mg/l. The maximum value is 25 mg/l in Mar. & Apr. 2013 at Gola Ghat while minimum value is 15 mg/l in July & Aug.. 2013 at Permut Ghat, which is below the prescribed limit (250 mg/l). The COD value of water were 25-39 mg/l. The maximum value is 40 mg/l in Dec. 2013 at Gola Ghat while minimum value is 25 mg/l in Aug.2013 at Permut Ghat.

The DO values were 4.2-7.4 mg/l. The maximum value is 7.4 in Dec.2013 at Permut Ghat while minimum value is 4.2 in March 2013 at Permut Ghat, which are permissible. The BOD values were 3.0-7.5 mg/l.The maximum value is 7.5 in Mar., May& Oct. 2013 at Gola Ghat while minimum value is 3.0 in Dec. 2013 at Permut Ghat.

Table-1 Physico-Chemical Characterstics in River Ganga at Gola Ghat, Kanpur

Month	Temperature ( <sup>0</sup> C)	Transparency (cm)	pН	DO (mg/l)	BOD (mg/l)	COD (mg/l)	Chloride (ppm)	Phosphate (mg/l)	Total hardness (mg/l)	TDS (mg/l)	Fluorid (mg/l)
Jan.	16.7	52.5	9.3	7.1	5.5	36	21	0.10	111.2	135	6.1
Feb.	18.7	52.5	9.2	6.9	5.5	35	22	0.12	107.4	136	6.1
Mar.	23.2	39.5	9.1	6.4	7.5	35	25	0.11	143.8	136	6.2
Apr.	31.1	36.5	8.3	6.6	7.0	35	25	0.14	155.1	135	6.1
May	35.6	20.5	8.2	5.2	7.5	38	23	0.08	160.1	136	6.0
Jun.	36.4	19.5	8.2	5.0	7.0	30	23	0.10	166.1	137	6.2
Jul.	28.4	22.0	8.2	5.4	6.5	36	19	0.05	98.9	139	6.3
Aug.	23.5	20.0	9.2	5.9	6.5	36	19	0.06	98.8	139	6.2
Sept.	24.2	25.0	8.9	6.2	7.0	35	18	0.06	96.6	138	6.1
Oct.	18.4	29.5	8.6	6.8	7.5	36	18	0.09	99.7	136	6.1
Nov.	18.6	37.0	9.1	7.0	6.0	35	19	0.10	110.4	136	6.2
Dec.	18.3	49.0	9.0	7.1	6.0	40	19	0.11	111.1	137	6.1

## International Journal of Advanced Technology in Engineering and Science Vol. No.3, Special Issue No. 01, September 2015

www.ijates.com

ISSN 2348 - 7550

Table-2 Physico-Chemical Characterstics in River Ganga at Permut Ghat, Kanpur

Month	Temperature	Transparency	pН	DO	BOD	COD	Chloride	Phosphate	Total	TDS	Fluorid
	( <sup>0</sup> C)	(cm)		(mg/l)	(mg/l)	(mg/l)	(ppm)	(mg/l)	hardness	(mg/l)	(mg/l)
									(mg/l)		
Jan.	16.2	54.5	8.8	7.0	6.5	37.0	18.0	0.14	110.2	135	6.2
Feb.	18.8	53.5	8.7	6.5	6.0	36.0	17.0	0.14	105.4	135	6.2
Mar.	23.4	40.0	8.5	4.2	6.0	36.0	17.0	0.14	136.6	136	6.1
Apr.	31.8	38.5	8.7	5.2	5.0	30.0	16.0	0.15	148.7	136	6.0
May	35.7	28.0	7.9	5.8	5.5	38.0	16.0	0.12	156.3	138	6.2
Jun.	36.2	22.0	8.0	6.1	6.5	29.0	15.0	0.16	160.9	139	6.3
Jul.	28.6	26.0	8.8	6.2	4.0	29.0	15.0	0.15	95.7	140	6.3
Aug.	23.4	22.0	8.9	6.5	4.0	28.0	15.0	0.16	96.3	138	6.2
Sept.	24.6	25.0	8.9	6.0	4.5	25.0	16.0	0.12	94.6	137	6.2
Oct.	18.3	27.5	8.4	6.8	3.5	36.0	17.0	0.9	95.6	136	6.1
Nov.	18.0	36.0	9.0	7.2	3.5	28.0	16.0	0.8	97.6	137	6.2
Dec.	18.4	50.5	9.1	7.4	3.0	36.0	18.0	0.9	98.6	137	6.1

#### IV. CONCLUSION

It is need of time to protect environment for present and future generation. The purpose of study is to prepare qualitative assessment of biotic and abiotic conditions prevailing in river Ganga.

#### **REFERENCES**

- [1]. American Public Health Association, American Water Works Association, and Water Pollution control Feseration, Standard methods for the examination of water and wastewater, 18<sup>th</sup> Ed. Washington D.C. USA, American Health Association variously paginated. 1992.
- [2]. ICMR Manual of standard of quality for drinking water supplies. ICMR, New Delhi. 1975.
- [3]. WHO (World Health Organization). Environmental health criteria, vol.134-Cadmium international programmed on Chemical Safety (IPCS) Monograph. Geneva, Switzerland.
- [4]. SI, Indian Standard Specification for drinking for water:ISI, 1983, 10500.
- [5]. Indian standard methods of sampling and test (Physical & chemical) for water used to industry, Indian Standard Institution ,New Delhi IS, 3025,1964.
- [6]. Rai,M. and Srivastava,R.M.,Metallic status in and around Chopan River Radhogarh,Cur.W.Envir.2006,1 (1) 91-93

## International Journal of Advanced Technology in Engineering and Science Vol. No.3, Special Issue No. 01, September 2015

www.ijates.com

ijates ISSN 2348 - 7550

- [7]. Rajesh C.V., Jitendra G. and Raghav S., Study of Physico-chemical characteristics and heavy metals in river Sengar at Jaswant Nagar District Etawah in Uttar Pradesh, Int. J. of pharm.res. and bio-sc. 2014, 3 (3) 108-111.
- [8]. Vishwakant, Verma, R.C. and Saxena, R.S., Study of some limnological properties of Harchandpur pond, District Etah, Cur. W. Envir., 2006, 2(1);35-38 (2007)
- [9]. Verma,R.C.,Mishra,P. and Sambhavi: Study of Phyco-chemical chaeacterstics river Ganga at Bithoor Ghat in Winter in District in Uttar Pradesh;GE-Int.J.Engg.Res.,2014,vol.-2,issue-5,125-128.
- [10]. Verma,R.C. and Bansal,A.:Study of Physico-chemical characteristics in river Ganga at Bithoor Ghat in District Kanpur in Uttar Pradesh,Am.Int.J. of Res. in Formal,Appl. And Nat.Sc.,2014,7(1),June-Aug.79-80.
- [11]. Verma,R.C.,Raghav,S.and Kumari,M.: Study of pollution ststus in River Ganga at Sarsaiya Ghat im District Kanpur in Uttar Pradesh, Int.J.of Adv.Tech.in Engg. And Sc.,2015,vol-3,spl.issue-02,Feb.,605-607.
- [12]. Elick,H.S. and Solomoon,R.J.: The Physico-chemical parameters of Souka River in the FCT Abuja,Int.J.of Bioassays,2015,4(07),4036-4049.
- [13]. Verma,R.C.,Raghav,S. and Kumari,O.: Study of physico-chemical characteristics in River Ganga at Sarsaiya Ghat and Gola Ghat in 2013 in District Kanpur in Uttar Pradesh,2015,vol.-4,spl.issue (01) Aug.2015,144-147.